

Productspecificaties P₂Liquid 3-9-3

Stikstof (N)	3 %
- Ammoniumstikstof	2.1%
- Ureum	0.6%
- Nitraat	0.3%
Fosfaat (P₂O₅)	9 %
Kalium (K₂O)	3 %
<hr/>	
pH (telquel)	tussen 3.3 – 4.3
Soortelijk gewicht (20°)	1.15
Cd (IPC-OES methode)	< 0,35 ppm
Opslagtemperatuur, niet onder	-2° C
Kg N/100 liter	3.5 %
Kg P₂O₅/100 liter	10.4 %
Kg K₂O/100 liter	3.5 %

Opmerkingen

- F2L Europe behoudt zich het recht voor tussentijdse wijzigingen aan te brengen in de eigenschappen en specificaties van de vermelde producten.
- Overige documentatie zoals safety datasheets en opslag & handling informatie kunt u vinden op de website van F2L Europe (www.f2leurope.com).

F₂L Europe BV

Burgemeester Visschersstraat 139, 6235 EB Ulestraten
Nederland

T +32 16448084
M +32 475414175
M +31 641785661
E info@f2leurope.com

All data, suggestions and information given herein is deemed to be accurate and reliable but is presented without warranty (expressed or implied) whatsoever. F2leurope BV does not accept any liability in connection with this information or use. It is the responsibility of each user to determine whether the information in this document is appropriate/suitable for their particular use, application or processing. Nothing in this document shall be deemed to alter or waive any provision of f2leurope's General Conditions of Sale or this disclaimer.